

Quick Compare - SNOWatHOME™ Snow Makers



SG4 Ubuild



SG6 X-Stream



SG7 X-Stream

Features

Maximum Snow Volume Output (cubic ft per hour)	60 ft ³ /hr	80 ft ³ /hr	225 ft ³ /hr
Stand	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Stand Adjustment	Ratcheting Gear Lock	Ratcheting Gear Lock	Ratcheting Gear Lock
Plume Illumination	yes	yes	yes
Adjustable Output	no	no	yes
High Pressure Liquid PSI Gauge	no	no	yes
Head Construction	Outer Aluminum Housing, Brass and Copper Internal components	Precision Machined Solid Aluminum	Precision Machined Solid Aluminum
Assembly Time	1-4 hours	5-10 mins	5-10 mins
Requirements for Operation			
1. Temperature Requirement	< 29°F	< 29°F	< 29°F
2. Pressure Washer / Pump			
Recommendation		SAH's 2.5gpm Pump	SAH's 2.5, 6.0, or 7.5gpm Snowmaking Pumps
Requirements	Electric or Gas	Electric or Gas	Electric or Gas
Gallons Per Minute (GPM)	1.3 - 2.1 gpm	1.3 - 2.5 gpm	1.3 - 8.0 gpm
PSI Range	1200 - 2500 psi	1200 - 4000 psi	1200 - 4000 psi
3. Air Compressor			
Recommendation	SAH's Air Compressor	SAH's Air Compressor	SAH's Air Compressor
Air Compressor Requirement	Electric or Gas	Electric or Gas	Electric or Gas
Lubrication	Oil Lubricated	Oil Lubricated	Oil Lubricated
Minimum Rating	5.4 cfm @ 90 psi	5.4 cfm @ 90 psi	5.4 cfm @ 90 psi