

## Quick Compare - SNOWatHOME® Snow Makers



SNO-PRO



SG6 X-Stream



SG7 X-Stream

### Features

Maximum Snow Volume Output (cubic ft per hour)	50 ft <sup>3</sup> /hr	80 ft <sup>3</sup> /hr	225 ft <sup>3</sup> /hr
Stand	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum
Stand Adjustment	no	Ratcheting Gear Lock	Ratcheting Gear Lock
Plume Illumination	optional light kit	yes	yes
Adjustable Output	no	no	yes
High Pressure Liquid PSI Gauge	no	no	yes
Head Construction	Precision Machined Solid Aluminum	Precision Machined Solid Aluminum	Precision Machined Solid Aluminum
Assembly Time	1-3 mins	5-10 mins	5-10 mins
<b>Requirements for Operation</b>			
1. Temperature Requirement	< 29°F	< 29°F	< 29°F
<b>2. Pressure Washer / Pump</b>			
Requirements	Electric or Gas	Electric or Gas	Electric or Gas
Gallons Per Minute (GPM)	1.3 - 1.7 gpm	1.3 - 2.5 gpm	1.3 - 8.0 gpm
PSI Range	1200 - 2500 psi	1200 - 4000 psi	1200 - 4000 psi
<b>3. Air Compressor</b>			
Air Compressor Requirement	Electric or Gas	Electric or Gas	Electric or Gas
Lubrication	Oil Lubricated	Oil Lubricated	Oil Lubricated
Minimum Rating	4.4 cfm @ 90 psi	5.4 cfm @ 90 psi	5.4 cfm @ 90 psi